

KABEL CU/PVC/PVC (NYY)

Jenis Kabel : Cu/PVC/PVC (NYY)		SPESIFIKASI KABEL									
Teg.Nom : 0,6 / 1 kV											
Standard : SNI IEC 60502											
Spesifikasi : Umum											
SIZE	Diameter Conductor	Isolasi		Diameter Filler	Sheathing		Berat total kabel		Kemasan Dus		
		Tebal Isolasi	Diameter Isolasi		Tebal Sheath	Diameter Sheath	kg/100m	kg/50m	50 m	100 m	
mm ²	mm	mm	mm	mm	mm	mm	mm	kg/100m	kg/50m	50 m	100 m
2 X 1.5	1.38	0.8	3.00	7.20	1.80	11.00	17.63	8.82	6	3	
2 X 2.5	1.78	0.8	3.40	8.00	1.80	11.70	21.18	10.59	5	3	
2 X 4	2.26	1.0	4.30	9.80	1.80	13.50	29.34	14.67	6	3	
2 X 6	2.76	1.0	4.85	10.90	1.80	14.60	36.29	18.14	4	2	
2 X 10	3.57	1.0	5.65	12.50	1.80	16.13	48.41	24.20	-	-	
2 X 16	5.19	1.0	7.19	16.39	1.80	19.99	74.25	37.13	6	3	
3 X 1.5	1.38	0.8	3.00	7.67	1.80	11.30	19.51	9.76	5	3	
3 X 2.5	1.78	0.8	3.40	8.53	1.80	12.20	24.43	12.22	4	3	
3 X 4	2.26	1.0	4.30	10.47	1.80	14.20	34.59	17.29	1	1	
3 X 6	2.76	1.0	4.85	11.65	1.80	15.26	43.03	21.51	1	1	
3 X 10	3.57	1.0	5.65	13.38	1.80	16.99	59.13	29.57	4	2	
3 X 16	5.19	1.0	7.19	17.51	1.80	21.11	90.74	45.37	-	-	
4 X 1.5	1.38	0.8	3.00	8.44	1.80	12.10	23.00	11.50	6	1	
4 X 2.5	1.78	0.8	3.40	9.41	1.80	13.10	29.15	14.57	4	3	
4 X 4	2.26	1.0	4.30	11.58	1.80	15.30	41.66	20.83	4	3	
4 X 6	2.76	1.0	4.85	12.91	1.80	16.52	52.49	26.25	4	4	
4 X 10	3.57	1.0	5.65	14.84	1.80	18.45	73.09	36.55	1	1	
4 X 16	5.19	1.0	7.19	19.37	1.80	22.97	112.26	56.13	1	1	

Keterangan:

- Pemuluran kawat : Min.25 %
- Resistivity at 20°C : Max. 17.241 Ω.mm²/km
- Warna Sheath : **HITAM**
- Warna Isolasi (*) : **B: biru muda, K : Kuning, H : Hitam, Hj-K : Hijau - Kuning**
- Kuat tarik isolasi/sheath : Min. 12.5 / 12.5 N/mm²
- Pemuluran isolasi/sheath : Min. 150 / 150 %
- AC.Test : 3.5 kV/ 5 min.
- Referensi : **SNI IEC 60502**

